

# INA PTUE25 bearing units

INA PTUE25 bearing units with easy-to-use parts graphics, giving you the ability to check parts N/A Minimum Buy Quantity availability, pricing, 0.0 Inventory examine remanufactured options.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 18.614   |
| EAN                       | 0883450354974  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                                      |
| Housing Style             | 2 Bolt Pillow Block                                    |
| Rolling Element           | Spherical Roller Bearing                               |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 24 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 22218  |
| Seals                     | Triple Lip Urethane                                    |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Single Collar   SN Style   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 90MM Bore; 112MM Base to Center Height; Concentric Collar Mount; Spherical Roll |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QASN18A090S0   |
| Weight / LBS                  | 56   |
| Bolt Spacing Maximum          | 12.874 Inch   327Millimeter  |
| d                             | 3.543 Inch   90 Millimeter   |
| B                             | 4.409 Inch   112 Millimeter  |
| D                             | 4.016 Inch   102 Millimeter  |
| Nominal Bolt Center to Center | 12.1 Inch   308.5 Millimeter   |
| Bolt Spacing Minimum          | 11.417 Inch   290Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |