

INA RASEL30-N bearing units

INA RASEL30-N bearing units Deal is your source for 40x17x12 Size (mm) OEM 17 Outer Diameter (mm) and accessories. 40 Bore Diameter (mm) We sell Genuine at discount prices.

Size (mm)	40x17x12
Bore Diameter (mm)	40
Outer Diameter (mm)	17
Width (mm)	12
d	17 mm
D	40 mm
B	12 mm
d1	26.25 mm
d2	21.66 mm
D1	31.15 mm
a	18 mm
r1,2 – min.	0.6 mm
r3,4 – min.	0.6 mm
da – min.	21.2 mm
Da – max.	35.8 mm
Db – max.	35.8 mm
ra – max.	0.6 mm
rb – max.	0.6 mm
Basic dynamic load rating – C	11 kN
Basic static load rating – C0	5.8 kN
Fatigue load limit – Pu	0.25 kN
Reference speed	22000 r/min
Limiting speed	22000 r/min

Calculation factor – kr	0.095
Calculation factor – ka	1.4
Calculation factor – e	1.14
Calculation factor – X	0.35
Calculation factor – Y0	0.26
Calculation factor – Y1	0.55
Calculation factor – Y2	0.57
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.073
EAN	7316571192635
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch – Metric	Metric
Long Description	17MM Bore; 40MM Outside Diameter; 12MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Ba

Other Features	Normal Axial Internal Clearance
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7203 BECBM
Weight / LBS	0.1609
Outside Diameter	1.575 Inch 40 Millimeter
Width	0.472 Inch 12 Millimeter
Bore	0.669 Inch 17 Millimeter
bore diameter:	17 mm
maximum temperature:	257 °F
outside diameter:	40 mm
cage material:	Brass
overall width:	12 mm
maximum rpm:	28000 rpm
contact angle:	40 °
finish/coating:	Uncoated
row type & fill slot:	Single-Row Non-Fill Slot
fillet radius:	0.6 mm
bore type:	Round
series:	7200
closure type:	Open
weight:	0.14 lb
bearing material:	Steel
manufacturer product page:	Click here
radial dynamic load capacity:	11 kN
manufacturer upc number:	7316571192635

radial static load capacity:	5.85 kN
d1 ≈	26.25 mm
d2 ≈	21.66 mm
D1 ≈	31.15 mm
r1,2 min.	0.6 mm
r3,4 min.	0.6 mm
da min.	21.2 mm
Da max.	35.8 mm
Db max.	35.8 mm
ra max.	0.6 mm
rb max.	0.6 mm
Basic dynamic load rating C	11 kN
Basic static load rating C0	5.85 kN
Fatigue load limit Pu	0.25 kN
Calculation factor A	0.000625
Calculation factor kr	0.095
Calculation factor e	1.14
Calculation factor X	0.57
Calculation factor Y0	0.52
Calculation factor Y2	0.93
Calculation factor Y1	0.55
Mass bearing	0.065 kg