INA RHE20 bearing units

170 FSNT 512-610 Housing Million used INA RHE20 bearing units instantly searchable. SR110X10 Locating Rings (width x OD) Shop our large selection of parts 22212K Bearing based on brand, price, description, and location. Order the with stock ...

HousingFSNT 512-610Bearing22212KLocating Rings (width x 0D)SR110X10SealTA512Seal TypeTaconiteAdapter Sleeve1H312LocknutKM12LockwasherEC512-610MaterialCast IronHousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169Max Oil Speed4400Shaft Diameter d55 mmA170 mmA3I65 mmGM12		1
Locating Rings (width x 0D)SR110X10SealTA512Seal TypeTaconiteAdapter SleevelH312LocknutKM12LockwasherMB12End Cover2EC512-610MaterialCast IronHousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Housing	FSNT 512-610
SealTA512Seal TypeTaconiteAdapter SleevelH312LocknutKM12LockwasherMB12End Cover2EC512-610MaterialCast IronHousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Bearing	22212K
Seal TypeTaconiteAdapter SleevelH312LocknutKM12LockwasherMB12End Cover2EC512-610MaterialCast IronHousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Locating Rings (width x OD)	SR110X10
Adapter SleevelH312LocknutKM12LockwasherMB12End Cover2EC512-610MaterialCast IronHousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Seal	TA512
LocknutKM12LockwasherMB12End Cover2EC512-610MaterialCast IronMousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA3165 mm	Seal Type	Taconite
LockwasherMB12End Cover2EC512-610MaterialCast IronMousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Adapter Sleevel	H312
End Cover2EC512-610MaterialCast IronHousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Locknut	KM12
MaterialCast IronHousing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Lockwasher	MB12
Housing Mass5.30 KgBolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	End Cover2	EC512-610
Bolt Qty4Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Material	Cast Iron
Cage TypeEJC1 Dynamic Load Rating169C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Housing Mass	5.30 Kg
C1 Dynamic Load Rating169C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Bolt Qty	4
C0 Static Load Rating174Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	Cage Type	EJ
Max Oil Speed5500Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	C1 Dynamic Load Rating	169
Max Grease Speed4400Shaft Diameter d55 mmA105.00 mmA170 mmA3165 mm	C0 Static Load Rating	174
Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Max Oil Speed	5500
A 105.00 mm A1 70 mm A3 165 mm	Max Grease Speed	4400
A1 70 mm A3 165 mm	Shaft Diameter d	55 mm
A3 165 mm	A	105.00 mm
	A1	70 mm
G M12	A3	165 mm
	G	M12

Н	134 mm
H1	70.0 mm
H2	30 mm
J	210.00 mm
J1	35 mm
J2	234 mm
L	255 mm
Ν	15 mm
N1	20.00 mm
UPC Code	999999999