

INA RNA030X42X32-ZW-ASR1 needle roller bearings

Request A Quote For Your Special INA RNA030X42X32-ZW-ASR1 needle roller bearings Needs Today! N/A Minimum Buy Quantity Free Quotes. 0.0 Inventory SKF Manufacturer Name ISO 9001 certified.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	2.096
EAN	7316577732422
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch – Metric	Metric
Long Description	60MM Straight Bore; 130MM Outside Diameter; 31MM Width; C0-Medium Clearance; Shaft Mount; Double Row
UNSPSC	31171510

Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	4.617
d	60 mm
D	130 mm
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
B	31 mm
bore diameter:	60 mm
maximum rpm:	6300 RPM
outside diameter:	130 mm
operating temperature range:	Maximum of +390 °F
overall width:	31 mm
cage material:	Steel
bore type:	Straight
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	31 mm
dynamic load capacity:	212 kN
fillet radius:	2 mm
static load capacity:	240 kN
series:	213

d2 ≈	87.8 mm
D1 ≈	115 mm
b	6 mm
K	3 mm
r1,2 min.	2.1 mm
da min.	72 mm
Da max.	118 mm
ra max.	2 mm
Basic dynamic load rating C	217 kN
Basic static load rating C0	240 kN
Fatigue load limit Pu	26.5 kN
Reference speed	4800 r/min
Limiting speed	6300 r/min
Calculation factor e	0.22
Calculation factor Y1	3
Calculation factor Y2	4.6
Calculation factor Y0	2.8
Mass bearing	2.1 kg