

INA RRY12-VA bearing units

INA RRY12-VA bearing units, Units and Housings CAD models , Manufacturing Service . Get Your 8 Days or more Days to Ship Free.

| | |
|-------------------------------------|----------------|
| Days to Ship | 8 Days or more |
| RoHS | 6 |
| Inner/Outer Ring Material | [Steel] Steel |
| Bearing Style | Rubber Sealed |
| Outer Ring Shape | Flat |
| Precision | Grade 0 |
| I.D.(Ø) | 80 |
| O.D.(Ø) | 140 |
| Width(mm) | 26 |
| Basic Dynamic Load Rating(N) | 72500 |
| Max. Allowed rpm(rpm) | 4500 |
| Rolling Element Material | [Steel] Steel |
| Retainer Type | Punching |
| Basic Load Rating, Static Rating(N) | 53000 |
| Clearance sign | CM |
| Accuracy(Class) | Class 0 |
| Acoustic Symbol | No |
| Grease Type | AS2S1 |
| Holder Symbol | No |
| Symbol of Bearing Ring Shape | No |
| Seal, Shield Symbols | VV |
| Precision Grade Symbol | No |
| Special Configurations Code | No |

| | |
|-----------------------------|-----------------|
| Rubugado Symbol | No |
| Material Symbol | No |
| Spacer, Sleeve symbol | No |
| Types | No |
| Type | Ball |
| Specifications, Environment | Standard |
| Load Direction | Radial |
| Outer Ring | With Outer Ring |
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| Combination symbol | No |
| Low Torque Specification | No |
| Internal Symbol | No |
| Torque Symbol | No |