INA RRY12-VA bearing units

INA RRY12-VA bearing units, Units and Housings CAD models , Manufacturing Service . Get Your 8 Days or more Days to Ship Free.

RoHS 6	s or more
ITILIEL/DULEL KILLU MALELIAL ISLEE	
	el] Steel
Bearing Style Rubbe	er Sealed
Outer Ring Shape Flat	
Precision Grade	e 0
I.D.(Ø) 80	
0.D.(Ø) 140	
Width(mm) 26	
Basic Dynamic Load Rating(N) 72500)
Max. Allowed rpm(rpm) 4500	
Rolling Element Material [Stee	el] Steel
Retainer Type Punch	ning
Basic Load Rating, Static Rating(N) 53000)
Clearance sign CM	
Accuracy(Class) Class	50
Acoustic Symbol No	
Grease Type AS2S1	L
Holder Symbol No	
Symbol of Bearing Ring Shape No	
Seal, Shield Symbols VV	
Precision Grade Symbol No	
Special Configurations Code No	

Rubugado Symbol	No
Material Symbol	No
Spacer, Sleeve symbol	No
Types	No
Туре	Ball
Specifications, Environment	Standard
Load Direction	Radial
Outer Ring	With Outer Ring
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Combination symbol	No
Low Torque Specification	No
Internal Symbol	No
Torque Symbol	No