

INA RSL183026-A cylindrical roller bearings

170 Million used INA RSL183026-A cylindrical roller bearings instantly searchable. Shop our large selection of parts 17 mm d based on brand, price, description, 35 mm D and location. Order the 10 mm B with stock ...

| | |
|---|------------|
| d | 17 mm |
| D | 35 mm |
| B | 10 mm |
| rs min | 0.3 mm |
| Radial clearance class | C3 |
| Mass | 0.04 kg |
| Dynamic load, C | 6.8 kN |
| Static load, C0 | 3.35 kN |
| Fatigue limit load, Cu | 0.15 kN |
| f0 | 13.6 |
| Nlim (grease) | 14,000 rpm |
| Min operating temperature, Tmin | -25 °C |
| Characteristic cage frequency, FTF | 0.39 Hz |
| Characteristic rolling element frequency, BSF | 4.47 Hz |
| Characteristic outer ring frequency, BPF0 | 3.14 Hz |
| Characteristic inner ring frequency, BRFI | 4.86 Hz |
| da min | 19 mm |
| da max | 21 mm |
| Da max | 33 mm |

| | |
|------------------------------|----------------------------|
| ra max | 0.3 mm |
| bore diameter: | 17 mm |
| precision rating: | ISO Class 0 |
| outside diameter: | 35 mm |
| finish/coating: | Uncoated |
| overall width: | 10 mm |
| bearing material: | High Carbon Chrome Steel |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Single Seal |
| inner ring width: | 10 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| outer ring width: | 10 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm (grease): | 14000 rpm |
| internal clearance: | C3 |
| fillet radius: | 0.3 mm |
| operating temperature range: | -40 to 120 °C |
| maximum rpm: | 24000 RPM |
| dynamic load capacity: | 6800 N |
| series: | 60 |
| static load capacity: | 3350 N |
| manufacturer product page: | Click here |