

# INA RSRD25-150-L0 bearing units

Request A Quote For Your Special INA RSRD25-150-L0 bearing units Needs Today! Free Quotes. ISO 130x150x30 Size (mm) 9001 certified.

Size (mm)	130x150x30
Bore Diameter (mm)	130
Outer Diameter (mm)	150
Width (mm)	30
Fw	130 mm
D	150 mm
C	30 mm
rmin	1 mm
m	730 g / Weight
Cr	112000 N / Dynamic load rating (radial)
C0r	239000 N / Static load rating (radial)
Cur	39000 N / Fatigue limit load, radial
nG	3600 1/min / Limiting speed
nB	2030 1/min / Reference speed
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.73
EAN	4012801405423
Product Group	B04144

Rolling Element	Needle Roller Bearing
Component	Roller Assembly with Outer Ring – No Inner Ring
Enclosure	Open
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	No
Inch – Metric	Metric
Relubricatable	Yes
Thrust Bearing	No
Long Description	130MM Bore; 150MM Outside Diameter; 30MM Width; Needle Roller Bearing; Roller Assembly with Outer Ri
Other Features	2 Rib Outer Ring   Precision   Steel Cage   Ground Raceway with Rib   Oil Hole
UNSPSC	31171512
Harmonized Tariff Code	8482.99.65.30
Noun	Roller Assembly with Outer Ring
Keyword String	Bearing Needle
Manufacturer Item Number	RNA4824
Weight / LBS	1.61
Width	1.181 Inch   30 Millimeter
Bore	5.118 Inch   130 Millimeter
Outside Diameter	5.906 Inch   150 Millimeter