

# INA SK104-207-KRR-B-AH12 deep groove ball bearings

Online shopping 80 mm da 76.2 mm dc INA SK104-207-KRR-B-AH12 deep groove ball bearings from a great selection at Store. 92.075 mm db ... Accessories.

da	80 mm
db	92.075 mm
dc	76.2 mm
Da	170 mm
Ca	67.793 mm
A1	98.425 mm
A2	160.338 mm
S	4.763 mm
ba	44.45 mm
H	209.55 mm
H1	107.95 mm
H2	44.45 mm
J min.	269.875 mm
J max.	320.675 mm
L	361.95 mm
N1	22.225 mm
R1	63.5 mm
R2	26.988 mm
RG	3/8 NPT
PG	1/8 NPT
h	42.862 mm
Housing	SAF 316

Bearing	22316 E
Lock nut	AN 16
Lock washer	W 16
Stabilizing ring	SR-19-16
Labyrinth ring (db shaft position)	LOR 84
PosiTrac Plus contact element (db shaft position)	B10724-106
Labyrinth ring (dc shaft position)	LOR 60
PosiTrac Plus contact element (dc shaft position)	B10724-184
End plug (suffix Y)	EPR 10
Max. speed for PosiTrac Plus seal	1450 r/min
P60°	85.9 kN
P90°	51.6 kN
P120°	32 kN
P150°	28.9 kN
P180°	34.7 kN
Pa	22.2 kN
Mass pillow block	30.4 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g