

# INA SL014952 cylindrical roller bearings

LET OUR INA SL014952 cylindrical roller bearings EXPERTS GET YOU THE 30.0 Inventory PARTS YOU NEED.

|                           |  |
|---------------------------|--|
| Inventory                 | 30.0   |
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 0.5  |
| EAN                       | 0662289543359  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | VS-116   |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Spherical   Intermediate Duty   Has Flinger                                   |
| Long Description          | 2 Bolt Pillow Block; 1" Bore; 1-7/16" Base to Center Height; Set Screw Mount; Ball Bearing |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | VPS-116M                       |
| Manufacturer Internal Number  | 767740                         |
| Weight / LBS                  | 1.1                            |
| D                             | 1.109 Inch   28.169 Millimeter |
| B                             | 1.438 Inch   36.525 Millimeter |
| Nominal Bolt Center to Center | 3.9 Inch   100 Millimeter      |
| d                             | 1 Inch   25.4 Millimeter       |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter           |
| Actual Bolt Center to Center  | 3.9 Inch   100Millimeter       |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter           |