

# ISB 21310 K+AHX310 spherical roller bearings

Request A Quote For Your Special ISB 21310 K+AHX310 spherical roller bearings 0.0 Inventory Needs Today! Free Quotes. ISO 9001 certified.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
UNSPSC	31000000
Weight	23.171
EAN	7316570373363
Product Group	M06288
inside diameter:	85 mm, 100 mm, 110 mm, 95 mm, 4.0000 in, 3.2500 in, 3.9375 in
housing material:	Cast Iron
base to bore centerline:	4.9375 in
compatible bearing type:	Spherical Roller
overall length:	16.1250 in
finish/coating:	Uncoated
overall height:	9.5000 in
compatible bearing series/part number:	1222 K, 2222 K, 23222CCK/W33, C2222 K, 1222, 1319, 1319 K, 21319 E, 21319 EK, 2222, 22222 E, 22
overall width:	6.9375 in
bolt center-to-center length:	13-11/16 in
mounting:	Two-Bolt Base

base width:	4-3/4 in
housing construction:	Split Pillow Block
series:	SNL
compatible bore diameter:	85 mm, 100 mm, 110 mm, 95 mm, 4.0000 in, 3.2500 in, 3.9375 in
standards met:	ISO/DIS 185 Grade 200
Bearing (basic designation)	22222 K
Adapter sleeve	H 322
Locating ring	2 x FRB 13.5/200
da	100 mm
Ca	80 mm
Da	200 mm
Db	147.5 mm
A	175 mm
A1	120 mm
H	242 mm
H1	125 mm
H2	45 mm
J	350 mm
L	410 mm
N	32 mm
N1	26 mm
J6	378 mm
J7	44 mm
N4 max.	8 mm
A2L	191 mm
A2T	250 mm
d2	182 mm

TSN 619 C TSN 6	2 x TSN 619 SE
P0°	600 kN
P55°	680 kN
P90°	410 kN
P120°	310 kN
P150°	275 kN
P180°	340 kN
Pa	220 kN
Q120°	620 kN
Q150°	360 kN
Q180°	310 kN
Mass housing	22 kg
Cap bolt, size	M 20×100
Cap bolt, rec. tightening torque	200 N·m
Appropriate attachment bolt, size G	24 mm
Appropriate attachment bolt, rec. tightening torque	665 N·m
Initial grease fill, 20%	530 g
Initial grease fill, 40%	850 g
TSN 522 C TSN 5	2 x TSN 522 SE
Lock nut	KM 19
Lock washer	MB 19
db	110 mm
TSN 319 A 2 x	2 x TK 319 ASNH
TSN 222 L TSN 2	2 x TK 222 ASNH
TSN 524 CE TSN	2 x TSN 522 SE