

ISB 2218 K+H318 self aligning ball bearings

How do I place an EMERGENCY 32052X Series order for a X32052X Cone Part Number ISB 2218 K+H318 self aligning ball bearings that I want to pick up at a our METRIC Design Units store?

Series	32052X
Cone Part Number	X32052X
Design Units	METRIC
Cage Type	Stamped Steel
C1 – Dynamic Radial Rating (Two-Row, 1 million revolutions) ¹	594000 lbf
C90(2) – Dynamic Radial Rating (Two-Row, 90 million revolutions) ²	154000 lbf
d	260 mm
B – Cone Width	87 mm
WPD	381.3 mm
DD	345.7 mm
R – Cone Backface To Clear Radius ³	5 mm
da – Cone Frontface Backing Diameter	284 mm
db – Cone Backface Backing Diameter	293 mm
Ab – Cage-Cone Frontface Clearance	5.3 mm
Aa – Cage-Cone Backface Clearance	9.9 mm
a – Effective Center Location ⁴	-1.5 mm
C90 – Dynamic Radial Rating (90 million revolutions) ⁵	394000 N
C1 – Dynamic Radial Rating (1 million revolutions) ⁶	1520000 N
C0 – Static Radial Rating	2440000 N

Ca90 – Dynamic Thrust Rating (90 million revolutions) ⁷	293000 N
K – Factor ⁸	1.34
G1 – Heat Generation Factor (Roller-Raceway)	1752.5
G2 – Heat Generation Factor (Rib-Roller End)	154
Cg – Geometry Factor	0.1711