

ISB 2219 K self aligning ball bearings

LET OUR ISB 2219 K self aligning ball bearings EXPERTS GET YOU THE Quote Days to Ship PARTS YOU NEED.

Days to Ship	Quote
RoHS	6
Inner/Outer Ring Material	[Steel] Steel
Bearing Style	Single Shielded
Outer Ring Shape	Flat
Precision	Grade 0
I.D.(Ø)	200
O.D.(Ø)	310
Width(mm)	51
Basic Dynamic Load Rating(N)	207000
Max. Allowed rpm(rpm)	1900
Rolling Element Material	[Steel] Steel
Retainer Type	Punching
Basic Load Rating, Static Rating(N)	226000
Clearance sign	CN (standard)
Accuracy(Class)	Class 0
Acoustic Symbol	No
Holder Symbol	No
Symbol of Bearing Ring Shape	No
Seal, Shield Symbols	ZS
Precision Grade Symbol	No
Special Configurations Code	No
Rubugado Symbol	No

Material Symbol	No
Spacer, Sleeve symbol	No
Types	No
Type	Ball
Specifications, Environment	Standard
Load Direction	Radial
Outer Ring	With Outer Ring
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Combination symbol	No
Low Torque Specification	No
Internal Symbol	No
Torque Symbol	No