

# ISB 22344 spherical roller bearings

High Quality ISB 22344 spherical roller bearings. 130 Outer Diameter (mm) Competitive 200x130x33 Size (mm) Pricing. Accept Small Order. 200 Bore Diameter (mm) Easy and Fast Shipping.

Size (mm)	200x130x33
Bore Diameter (mm)	200
Outer Diameter (mm)	130
Width (mm)	33
d	130 mm
D	200 mm
B	33 mm
D1	175.2 mm
F	148 mm
r1,2 – min.	2 mm
r3,4 – min.	1.1 mm
s	4.7 mm
da – min.	137 mm
da – max.	145 mm
db – min.	151 mm
Da – max.	191 mm
ra – max.	2 mm
rb – max.	1 mm
Basic dynamic load rating – C	165 kN
Basic static load rating – C0	224 kN
Fatigue load limit – Pu	25 kN
Reference speed	3800 r/min

Limiting speed	5600 r/min
Calculation factor – kr	0.15
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.923
EAN	7316577065254
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	130MM Bore; Straight Bore Profile; 200MM Outside Diameter; 33MM Width; Brass Cage Matetrial; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing

Manufacturer Item Number	NU 1026 ML
Weight / LBS	8.64
Bore	5.118 Inch   130 Millimeter
Width	1.299 Inch   33 Millimeter
Outside Diameter	7.874 Inch   200 Millimeter
D1 ≈	175.2 mm
r1,2 min.	2 mm
r3,4 min.	1.1 mm
s max.	4.7 mm
da min.	137 mm
da max.	145 mm
db min.	151 mm
Da max.	191 mm
ra max.	2 mm
rb max.	1 mm
Basic dynamic load rating C	165 kN
Basic static load rating C0	224 kN
Fatigue load limit Pu	25 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	3.84 kg