

ISB 230/1060 EKW33+A0H30/1060 spherical roller bearings

Find the discount ISB 230/1060 EKW33+A0H30/1060 spherical roller bearings online 15.0 Inventory you need . We offer ... If you check out our large selection of ISB 230/1060 EKW33+A0H30/1060 spherical roller bearings once .

Inventory	15.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	27 lb
EAN	0053893534510
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 2-15/16" Bore; 8-1/2" Bolt Circle; 6" Bolt Spacing; 1 Pie

Other Features	Double Row Wide Inner Race With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	E-4BF-TRB-2 15/16
Weight / LBS	27
Nominal Bolt Circle Diameter Round	8.5 Inch 215 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
D	4.5 Inch 114.3 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
d	2.938 Inch 74.625 Millimeter
Bolt Spacing	6 Inch 152.4 Millimeter
Shaft Size	2.9375 in
Shaft Size Type	Imperial
UPC Code	053893534510
Dimension B	4-1/2 in
Dimension L	7-3/4 in
Dimension A	3-15/16 in
Dimension J	6 in
Dimension A2	3/16 in
Bolt Diameter	3/4 in
Dimension A1	1-5/8 in
Dimension D 1	6 in
Dimension d1	4-23/32 in
e	0.46
X (if $F_a/F_r \leq e$)	0.87

Y (if $F_a/F_r \leq e$)	1.87
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.26
K Factor	1.30
C90 Dynamic Load Rating ²	12300 lb
C0 Static Load Rating	61200 lb
Fa-max Maximum Permissible Thrust Load ³	5181 lb
Fr-max Maximum Allowable Slip Fit Radial Load ⁴	10000 lb
Max. Speed ⁵	2060 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to