

ISB 2316 K self aligning ball bearings

What is ISB 2316 K self aligning ball bearings in mechanical C 3184 K Bearing (basic designation) engineering? Manufacturing 0H 3184 H Adapter sleeve Service . Upload your CAD file for an instant.

Bearing (basic designation)	C 3184 K
Adapter sleeve	0H 3184 H
Locating ring	2 x FRB 10/700
da	400 mm
Ca	244 mm
Da	700 mm
A	455 mm
A1	420 mm
H	810 mm
H1	410 mm
H2	130 mm
J	1000 mm
J1	260 mm
L	1170 mm
N	60 mm
N1	48 mm
s	35 mm
ba min.	207 mm
ba max.	238 mm
bb	202 mm
bc	243.5 mm

J6	1070 mm
N4 max.	35 mm
Oil seal	TSD 3184 U
End cover	ETS 3176 R
P0°	7600 kN
P55°	9600 kN
P90°	4600 kN
P120°	3400 kN
P150°	3000 kN
P180°	3800 kN
Q120°	5800 kN
Q150°	3350 kN
Q180°	2900 kN
Mass housing	709 kg
Cap bolt, size	M 42×280
Cap bolt, rec. tightening torque	850 N·m
Appropriate attachment bolt, size G	42 mm
Appropriate attachment bolt, rec. tightening torque	3640 N·m
Eye bolt, size	2 x M 42
Oil level, min.	103 mm
Oil level, max.	129 mm