

ISB 2320 K+H2320 self aligning ball bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all 73x35x37 Size (mm) your ISB 2320 K+H2320 self aligning ball bearings needs – including routine maintenance, major repairs, warranty service, and equipment inspections.

Size (mm)	73x35x37
Bore Diameter (mm)	73
Outer Diameter (mm)	35
Width (mm)	37
d	35 mm
D	73 mm
H	37 mm
D1	47 mm
B	9 mm
r1,2 – min.	1 mm
r3,4 – min.	0.6 mm
da	45 mm
Da – max.	56 mm
ra – max.	1 mm
rb – max.	0.6 mm
Basic dynamic load rating – C	39 kN
Basic static load rating – C0	86.5 kN
Fatigue load limit – Pu	3.2 kN
Reference speed	2600 r/min
Limiting speed	3600 r/min

Minimum load factor – A	0.038
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.621
EAN	7316577007117
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Double Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Double Row
Long Description	35MM Bore 1; 47MM Bore 2; 73MM Outside Diameter; 37MM Height; Ball Bearing; Double Direction; Not Ba
Inch – Metric	Metric
UNSPSC	31171507
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	52209
Weight / LBS	1.367
Bore 1	1.378 Inch 35 Millimeter
Outside Diameter	2.874 Inch 73 Millimeter
Height	1.457 Inch 37 Millimeter

Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 2	1.85 Inch 47 Millimeter
bore diameter:	35 mm
static load capacity:	86.5 kN
outside diameter:	73 mm
dynamic load capacity:	39 kN
overall width:	37 mm
maximum rpm:	3600 RPM
thrust bearing type:	Double-Direction
cage material:	Steel
outside diameter design:	Straight
fillet radius:	0.6 mm
separable or banded:	Separable
series:	522
precision rating:	ABEC 1 (ISO Class Normal)
D1 ≈	47 mm
r1,2 min.	1 mm
r3,4 min.	0.6 mm
Da max.	56 mm
ra max.	1 mm
rb max.	0.6 mm
Basic dynamic load rating C	39 kN
Basic static load rating C0	86.5 kN
Fatigue load limit Pu	3.2 kN
Minimum load factor A	0.038
Mass bearing (including seat washer where applicable)	0.6 kg