

ISB 24034 spherical roller bearings

ISB 24034 spherical roller bearings SEARCH – Whether it's agriculture or construction equipment your working on, Has the 61.913 mm da you need.

da	61.913 mm
Da	130 mm
Ca	37.008 mm
A1	79.375 mm
A2	193.675 mm
ba	30.163 mm
H	157.559 mm
H1	82.55 mm
H2	28.575 mm
J min.	219.075 mm
J max.	244.475 mm
L	285.75 mm
N1	19.05 mm
R1	46.038 mm
R2	21.431 mm
RG	1/4 NPT
PG	1/8 NPT
h	31.75 mm
Housing	SAF 515
Bearing	1215 K
Adapter sleeve assembly	SNW 15×2.7/16
Stabilizing ring	2 x SR-15-0

Taconite seal	TER 37
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1250 r/min
P60°	75.6 kN
P90°	45.4 kN
P120°	28 kN
P150°	25.4 kN
P180°	30.2 kN
Pa	5.65 kN
Mass pillow block	13.1 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	81.3 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	136.08 g