

ISB 29424 M thrust roller bearings

What is ISB 29424 M thrust roller bearings 8 Days or more Days to Ship in mechanical engineering? Manufacturing Service . Upload your CAD file for an instant.

| | |
|--|-----------------|
| Days to Ship | 8 Days or more |
| RoHS | 6 |
| Bearing Style | Double Shielded |
| d | 90 |
| D | 115 |
| B | 13 |
| Basic Dynamic Load Rating Cr(N) | 19000 |
| Allowable Rotational Velocity(Grease Lubrication)(rpm) | 5400 |
| Basic Static Load Rating Cor(N) | 19700 |
| Sealing Structure | Double Shielded |
| Type | Ball |
| Bearing Ring Material | Steel |
| Outer Ring Shape | Flat |
| Precision | Grade 0 |
| Specifications, Environment | Standard |
| Load Type | Radial |
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| Transmitter Material | Steel |
| Retainer Type | Punching |
| Inner/Outer Ring Material | [Steel] Steel |

| | |
|-------------------------------------|-----------------|
| I.D.(Ø) | 90 |
| O.D.(Ø) | 115 |
| Width(mm) | 13 |
| Basic Dynamic Load Rating(N) | 19000 |
| Max. Allowed rpm(rpm) | 5300 |
| Rolling Element Material | [Steel] Steel |
| Basic Load Rating, Static Rating(N) | 21000 |
| Clearance sign | CN (standard) |
| Accuracy(Class) | Class 0 |
| Acoustic Symbol | No |
| Holder Symbol | No |
| Symbol of Bearing Ring Shape | No |
| Seal, Shield Symbols | ZZ |
| Precision Grade Symbol | No |
| Special Configurations Code | No |
| Rubugado Symbol | No |
| Material Symbol | No |
| Spacer, Sleeve symbol | No |
| Types | No |
| Load Direction | Radial |
| Outer Ring | With Outer Ring |
| Combination symbol | No |
| Low Torque Specification | No |
| Internal Symbol | No |
| Torque Symbol | No |
| Specifications/Environment | Standard |