

ISB 591/950 thrust ball bearings

Welcome 20 Outer Diameter (mm) to the 30 Bore Diameter (mm) ISB 591/950 thrust ball bearings online seller. 30x20x30 Size (mm)

Size (mm)	30x20x30
Bore Diameter (mm)	30
Outer Diameter (mm)	20
Width (mm)	30
Fw	20 mm
D	30 mm
C	30 mm
C1	10 mm
C2	10.5 mm
d	20 mm
D2	36.2 mm
r _{1,2} – min.	0.3 mm
da – min.	30.7 mm
ra – max.	0.3 mm
rb – max.	0.3 mm
d _i	17 mm
F	20 mm
B _i	20 mm
Basic dynamic load rating, radial direction – C	16.5 kN
Basic static load rating, radial direction – C0	25.5 kN
Basic dynamic load rating, axial direction – C	18.6 kN
Basic static load rating, axial direction – C0	48 kN

Fatigue load limit, radial direction – Pu	3 kN
Fatigue load limit, axial direction – Pu	4.6 kN
Reference speed	3800 r/min
Limiting speed	7500 r/min
Mass bearing	0.084 kg
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.084
Product Group	B04144
r1,2 min.	0.3 mm
da min.	30.7 mm
ra max.	0.3 mm
rb max.	0.3 mm
Basic dynamic load rating, radial direction C	16.5 kN
Basic static load rating, radial direction C0	25.5 kN
Basic dynamic load rating, axial direction C	18.6 kN
Basic static load rating, axial direction C0	48 kN
Fatigue load limit, radial direction Pu	3.05 kN
Fatigue load limit, axial direction Pu	4.65 kN
Minimum axial load factor A	0.000184
Inner ring	IR 17x20x20