

# ISB 61801-ZZ deep groove ball bearings

Request A 111.125 mm da 279.999 mm Da Quote For Your Special ISB 61801-ZZ deep groove ball bearings Needs Today! Free Quotes. ISO 9001 certified.

da	111.125 mm
Da	279.999 mm
Ca	102.794 mm
A1	158.75 mm
A2	222.25 mm
S	4.763 mm
ba	72.231 mm
H	336.55 mm
H1	169.875 mm
H2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J1	95.25 mm
L	558.8 mm
N1	28.575 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	61.913 mm
Housing	SAF 626
Bearing	22326 CCK/W33

Adapter sleeve assembly	SNW 126×4.3/8
Stabilizing ring	SR-0-26
Labyrinth ring	2 x LOR 116
End plug (suffix Y)	EPR 15
Bearing limiting speed	2400 r/min
P60°	226 kN
P90°	136 kN
P120°	85.9 kN
P150°	78.3 kN
P180°	94.3 kN
Pa	36.3 kN
Mass pillow block	108 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g