

ISB 6308-RS deep groove ball bearings

ISB 6308-RS deep groove ball bearings 14 mm B Industries 20 mm d and Applications ? We 47 mm D sell discount online as well as cheap machinery parts.

d	20 mm
D	47 mm
B	14 mm
rs min	1 mm
Radial clearance class	C2
Mass	0.11 kg
Dynamic load, C	12.8 kN
Static load, C ₀	6.65 kN
Fatigue limit load, C _u	0.3 kN
f ₀	13.2
N _{lim} (oil)	18,000 rpm
N _{lim} (grease)	16,000 rpm
Min operating temperature, T _{min}	-20 °C
Max operating temperature, T _{max}	120 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.12 Hz
Characteristic outer ring frequency, BPF ₀	3.08 Hz
Characteristic inner ring frequency, BPFI	4.92 Hz
da min	25 mm
Da max	42 mm

ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.105
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C2-Snug
Inch – Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.234
Bore	0.787 Inch 20 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
Outer Race Width	0.551 Inch 14 Millimeter