

ISB EB1.25.0755.200-1STPN thrust ball bearings

ISB EB1.25.0755.200-1STPN thrust ball bearings with easy-to-use parts graphics, 71.425 mm dc giving 87.325 mm db you the ability to check 75 mm da parts availability, pricing, examine remanufactured options.

da	75 mm
db	87.325 mm
dc	71.425 mm
Da	160 mm
Ca	64.795 mm
A1	98.425 mm
A2	230.188 mm
S	4.763 mm
ba	44.45 mm
H	192.088 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
J1	53.975 mm
L	349.25 mm
N1	19.05 mm
R1	60.325 mm
R2	27.94 mm
RG	3/8 NPT
PG	1/8 NPT

h	40.481 mm
Housing	FSAF 315
Bearing	22315 E
Lock nut	AN 15
Lock washer	W 15
Stabilizing ring	SR-18-15
Taconite seal (db shaft position)	TER 79
Taconite seal (dc shaft position)	TER 46
End plug (suffix Y)	EPR 8
Max. speed for Taconite seal	900 r/min
P60°	101 kN
P90°	60.9 kN
P120°	38.3 kN
P150°	34.7 kN
P180°	42.3 kN
Pa	27.1 kN
Mass pillow block	24 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	141.75 g