

# ISB F692 deep groove ball bearings

Advance ISB F692 deep groove ball bearings is your source for 0.0 Inventory quality and accessories. shop online for home delivery or pick up in one of our 10000 .

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 36.77  |
| EAN                       | 0087796075061  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Shaft Mount  |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22222  |
| Seals                     | Triple Ring Labyrinth  |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Straight Bore   |
| Long Description          | 4 Bolt Pillow Block; 4.331" Bore; 4-15/16" Base to Center Height; Shaft Mount Mount; Spher |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | SAF 22222                       |
| Weight / LBS                  | 81                              |
| Bolt Spacing Minimum          | 12.625 Inch   320.675Millimeter |
| d                             | 4.331 Inch   110.007 Millimeter |
| D                             | 2.00 in                         |
| B                             | 16.5 in                         |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| Nominal Bolt Center to Center | 13.6 Inch   344.5 Millimeter    |
| Bolt Spacing Maximum          | 14.5 Inch   368.3Millimeter     |
| Diameter S-2                  | 4 7/8 in                        |
| Diameter S-3                  | 4 3/16 in                       |
| A                             | 4.9375 in                       |
| C                             | 4.750 in                        |
| E Max.                        | 14.5000 in                      |
| E Min.                        | 12.6250 in                      |
| F                             | 2.75 in                         |
| H1                            | 9.5625 in                       |
| Oil Level K                   | 1.8750 in                       |
| L2                            | 6.3750 in                       |
| Y                             | 1.9531 in                       |
| No. of Base Bolts Required    | 4                               |
| Size of Base Bolts Required   | 3.4 in                          |
| Locknut                       | AN22                            |
| Lockwasher                    | W22                             |
| Housing Only3                 | SAF222                          |

|                            |                  |
|----------------------------|------------------|
| Bolt Hole Length           | 1.6875 in        |
| Bolt Hole Width            | 0.750 in         |
| Stabilizing Ring 1 Req'd4  | SR-22-19         |
| Triple Seal 2 Req'd at S-2 | LOR121           |
| Triple Seal 2 Req'd at S-3 | LOR113           |
| Assembly Weight            | 81.000 lb        |
| Full Timken Part Number    | SAF22222         |
| Seal Type                  | Triple Ring Seal |