

ISB FCDP 140200710 cylindrical roller bearings

Can't find what you're looking for ISB FCDP 140200710 cylindrical roller bearings ? Our expert Representatives be in contact with you 31.75 Bore Diameter (mm) shortly!

Bore Diameter (mm)	31.75
d	31.75 mm
s1	25.4 mm
A	41 mm
A1	27 mm
B	42,9 mm
G	10 mm
H	78 mm
H1	39.3 mm
H2	5 mm
J	106 mm
L	130 mm
N	11,2 mm
Weight	0,73 Kg
Basic dynamic load rating (C)	25,5 kN
Basic static load rating (C0)	15,3 kN
Housing material	Pressed steel
B4	6 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C0	15.3 kN
Fatigue load limit Pu	0.655 kN
Permissible radial housing load max.	3.3 kN

Limiting speed	5300 r/min
Mass bearing unit	0.79 kg
Thread grub screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	P 72
Bearing	YAR 207-104-2F