

# ISB GAC 30 CP plain bearings

Offer High 35x90x32 Size (mm) Quality Brand ISB GAC 30 CP plain bearings .Contact Us Online to Get Best Quote.

Size (mm)	35x90x32
Bore Diameter (mm)	35
Outer Diameter (mm)	90
Width (mm)	32
d	35 mm
D	90 mm
H	32 mm
d1	80 mm
r1 min.	1,1 mm
r2 min.	1,1 mm
D1	37 mm
da min.	62 mm
Da max.	53 mm
ra max.	1 mm
Weight	0,79 Kg
Basic dynamic load rating (C)	76,1 kN
Basic static load rating (C0)	137 kN
Fatigue load limit (Pu)	5,1
Reference speed	2600 r/min
Limiting speed	3600 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.764

EAN	7316576677984
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1   ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row
Long Description	35MM Bore 1; 37MM Bore 2; 80MM Outside Diameter; 32MM Height; Ball Bearing; Single Direction; Not Ba
Inch – Metric	Metric
UNSPSC	31171507
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	51407
Weight / LBS	1.682
Bore 2	1.457 Inch   37 Millimeter
Outside Diameter	3.15 Inch   80 Millimeter
Overall Height with Aligning Washer	0 Inch   0 Millimeter
Height	1.26 Inch   32 Millimeter
Bore 1	1.378 Inch   35 Millimeter
bore diameter:	35 mm
static load capacity:	137 kN
outside diameter:	90 mm

dynamic load capacity:	76.1 kN
overall width:	32 mm
maximum rpm:	3600 RPM
thrust bearing type:	Single-Direction
cage material:	Steel
outside diameter design:	Straight
fillet radius:	1 mm
separable or banded:	Separable
series:	514
precision rating:	ABEC 1 (ISO Class Normal)
d1 ≈	80 mm
D1 ≈	37 mm
r1,2 min.	1.1 mm
Basic dynamic load rating C	76.1 kN
Basic static load rating C0	137 kN
Fatigue load limit Pu	5.1 kN
Minimum load factor A	0.15
Mass bearing (including seat washer where applicable)	0.79 kg