

# ISB GE 360 CP plain bearings

ISB GE 360 CP plain bearings TIMKEN Manufacturer Name Needs 0.0 Inventory Analysis , N/A Minimum Buy Quantity Manufacturing Service . Get Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 9.988  |
| EAN                       | 0883450153027  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22213  |
| Seals                     | Triple Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Nut   SAF Style  |
| Long Description          | 4 Bolt Pillow Block; 2-1/4" Bore; 3" Base to Center Height; V Lock Mount; Spherical Roller |
| UNSPSC                    | 31171511   |

|                               |                               |
|-------------------------------|-------------------------------|
| Harmonized Tariff Code        | 8483.20.40.80                 |
| Noun                          | Bearing                       |
| Keyword String                | Pillow Block                  |
| Weight / LBS                  | 22                            |
| B                             | 3 Inch   76.2 Millimeter      |
| D                             | 3.36 Inch   85.344 Millimeter |
| Nominal Bolt Center to Center | 7.9 Inch   199.5 Millimeter   |
| d                             | 2.25 Inch   57.15 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter          |
| Bolt Spacing Minimum          | 7.18 Inch   182.372Millimeter |
| Bolt Spacing Maximum          | 8.56 Inch   217.424Millimeter |