

# ISB NB1.25.1455.201-2PPN thrust ball bearings

ISB NB1.25.1455.201-2PPN thrust ball bearings Engineering Calculator , 200 mm Da Manufacturing Service . Get 111.125 mm da Your Free.

da	111.125 mm
Da	200 mm
Ca	62.789 mm
A1	120.65 mm
A2	165.1 mm
ba	51.594 mm
H	244.475 mm
H1	125.425 mm
H2	52.388 mm
L	419.1 mm
R1	73.025 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	40.922 mm
Housing	SSAFS 026 KA
Bearing	23026 CCK/W33
Adapter sleeve assembly	SNW 3026×4.3/8
Stabilizing ring	2 x 38151-26
Labyrinth ring	2 x LOR 116
PosiTrac Plus contact element	2 x B10724-117
End plug (suffix Y)	EPR 15

Max. speed for PosiTrac Plus seal	1300 r/min
P60°	178 kN
P90°	107 kN
P120°	66.7 kN
P150°	59.6 kN
P180°	72.5 kN
Pa	20.2 kN
Mass pillow block	52.2 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	232.47 g