

ISB NBL.30.1455.200-1PPN thrust ball bearings

High Quality ISB NBL.30.1455.200-1PPN thrust ball bearings. Competitive Pricing. Accept Small Order. Easy and Fast Shipping. 107.95 mm da

da	107.95 mm
Da	215.001 mm
Ca	67.793 mm
A1	120.65 mm
A2	254 mm
S	4.763 mm
ba	53.181 mm
H	257.175 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	79.375 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	46.831 mm
Housing	SAF 524
Bearing	22224 EK

Adapter sleeve assembly	SNW 24×4.1/4
Stabilizing ring	SR-24-20
Taconite seal	TER 114
End plug (suffix Y)	EPR 14
Max. speed for Taconite seal	725 r/min
P60°	185 kN
P90°	111 kN
P120°	72.5 kN
P150°	66.7 kN
P180°	81.4 kN
Pa	20.7 kN
Mass pillow block	47.2 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	379.89 g