

# ISB NN 3009 TN/SP cylindrical roller bearings

With over 10170 full-service stores, our ISB NN 3009 TN/SP cylindrical roller bearings inventory is extensive and our parts are priced right. 0.0 Inventory within N/A Minimum Buy Quantity 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | IPTCI BEARINGS   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 2.766  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 2 Bolt Pillow Block                                      |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | NA209-26   |
| Seals                     | B Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Standard Duty   Wide Inner Race   High Base |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 1-5/8" Bore; 2-1/8" Base to Center Height; Eccentric Collar Mount; Ba |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | NAP 209 26   |
| Weight / LBS                  | 6.1  |
| Actual Bolt Center to Center  | 5.8 Inch   146.1Millimeter   |
| B                             | 2.125 Inch   53.98 Millimeter  |
| d                             | 1.625 Inch   41.275 Millimeter   |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter   |
| Nominal Bolt Center to Center | 5.8 Inch   146.5 Millimeter  |
| D                             | 2.217 Inch   56.3 Millimeter   |