

ISB NN 3017 TN9/SP cylindrical roller bearings

How do you find 23,813 Bore Diameter (mm) the ISB NN 3017 TN9/SP cylindrical roller bearings specification? Manufacturers Online Free check

Bore Diameter (mm)	23,813
d	23,813 mm
V	80,01 mm
U	38,811 mm
Thread (Q)	1/8 NPT
A	30,505 mm
A1	13,005 mm
B	34,112 mm
J	70,002 mm
L	95,504 mm
N	11,506 mm
A2	18,999 mm
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.9
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron

Expansion / Non-expansion	Non-expansion
Mounting Bolts	29/64 Inch
Relubricatable	Yes
Insert Part Number	GY1015KRRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 15/16" Bore; 4" Bolt Circle; 2.756" Bolt Spacing; 1 Piece
Other Features	Single Row With Grub Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	RCJY15/16
Weight / LBS	1.985
Bore	0.938 Inch 23.825 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Nominal Bolt Circle Diameter Round	4 Inch 101.6 Millimeter
Bolt Spacing	2.756 Inch 70 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Length Thru Bore	1.343 Inch 34.1 Millimeter