

ISB NU 1009 cylindrical roller bearings

How do you find 180.975 mm da the 147.803 mm Ca ISB NU 1009 cylindrical roller bearings specification? Manufacturers Online Free check

da	180.975 mm
Da	419.999 mm
Ca	147.803 mm
A1	228.6 mm
A2	317.5 mm
S	4.763 mm
ba	103.188 mm
H	495.3 mm
H1	250.825 mm
H2	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
J1	139.7 mm
L	869.95 mm
N1	41.275 mm
R1	163.512 mm
R2	50.8 mm
RG	1 NPT
PG	1/4 NPT
h	87.313 mm
Housing	SAFS 640
Bearing	22340 CCK/W33

Adapter sleeve assembly	SNW 140×7.1/8
Stabilizing ring	SR-0-40
Labyrinth ring	2 x LOR 664
End plug (suffix Y)	EPR 21
Bearing limiting speed	1500 r/min
P60°	669 kN
P90°	400 kN
P120°	249 kN
P150°	222 kN
P180°	267 kN
Pa	82.7 kN
Mass pillow block	431 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g