

# ISB RE 19025 thrust roller bearings

100% Authentic. 40 Bore Diameter (mm) ISB RE 19025 thrust roller bearings Highest 40x30x29 Size (mm) Quality. Certified Supplier.

Size (mm)	40x30x29
Bore Diameter (mm)	40
Outer Diameter (mm)	30
Width (mm)	29
d	30 mm
A	40 mm
A1	29 mm
H	23.5 mm
H1	42.9 mm
H2	16.5 mm
L	152 mm
J	117.5 mm
N1	14 mm
B	38.1 mm
s1	22.2 mm
Basic dynamic load rating – C	19.5 kN
Basic static load rating – C0	11.2 kN
Limiting speed	190 r/min
Limiting temperature – T	350 °C
Mass bearing unit	1.1 kg
Grub (set) screw – G2	M6x0.75

Hexagonal key size for grub screw – H	3 mm
Recommended tightening torque for grub screw	4 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.1
EAN	7316571382357
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	12 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 206-2F/VA228
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Metric
Other Features	Single Row   Standard Duty   Wide Inner Race   High Temperature Bearing with Graphite   Y Bearing
Long Description	2 Bolt Pillow Block; 30MM Bore; 42.9MM Base to Center Height; Set Screw Mount; Ball Bearing; Relubri
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 30 TF/VA228
Weight / LBS	2.43
Base to Center Height	1.689 Inch   42.9 Millimeter
Bolt Spacing Minimum	0 Inch   0Millimeter
Bore	1.181 Inch   30 Millimeter
Nominal Bolt Center to Center	4.8 Inch   121 Millimeter
Length Thru Bore	1.5 Inch   38.1 Millimeter
Bolt Spacing Maximum	0 Inch   0Millimeter
Actual Bolt Center to Center	4.6 Inch   117.5Millimeter
mounting:	Two-Bolt Base
overall height:	82.5 mm
bore diameter:	30 mm
finish/coating:	Uncoated
bore type:	Round
radial static load capacity:	11.2 kN
base to bore centerline:	1.6890 in
base width:	40 mm
housing material:	Cast Iron
bolt center-to-center length:	117.5 mm
locking device:	Set Screw
lubrication type:	Lubrication Fitting
expansion type:	Non-Expansion Bearing (Fixed)
series:	SY
overall length:	152 mm

standards met:	ISO
N	23.5 mm
Basic dynamic load rating C	19.5 kN
Basic static load rating C0	11.2 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	M6x0.75
Hexagonal key size for grub screw N	3 mm
Attachment bolts, recommended metric size G	12 mm
Bearing	YAR 206-2FW/VA228