

ISB SA 80 C 2RS plain bearings

ISB SA 80 C 2RS plain bearings Engineering Calculator , 53.975 mm db 45 mm da 42.875 mm dc Manufacturing Service . Get Your Free.

da	45 mm
db	53.975 mm
dc	42.875 mm
Da	100 mm
Ca	45.796 mm
A1	69.85 mm
A2	180.975 mm
ba	25.4 mm
H	134.938 mm
H1	69.85 mm
H2	25.4 mm
J min.	187.325 mm
J max.	200.025 mm
L	244.475 mm
N1	19.05 mm
R1	38.1 mm
R2	17.462 mm
RG	1/8 NPT
PG	1/8 NPT
h	33.337 mm
Housing	SAF 309
Bearing	1309 ETN9

Lock nut	N 09
Lock washer	W 09
Stabilizing ring	2 x SR-1609
Taconite seal (db shaft position)	TER 28
Taconite seal (dc shaft position)	TER 20
End plug (suffix Y)	EPR 4
Max. speed for Taconite seal	1450 r/min
P60°	35.1 kN
P90°	20.9 kN
P120°	13.3 kN
P150°	12 kN
P180°	14.7 kN
Pa	9.34 kN
Mass pillow block	8.35 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	82.215 g