

# ISB SI 35 ES plain bearings

Online shopping 203.2 mm da ISB SI 35 ES plain bearings from a great selection at Store. ... Accessories. 101.803 mm Ca

da	203.2 mm
Da	339.999 mm
Ca	101.803 mm
A1	190.5 mm
A2	276.225 mm
ba	80.169 mm
H	400.05 mm
H1	200.025 mm
H2	79.375 mm
L	711.2 mm
R1	120.65 mm
R2	42.069 mm
RG	1 NPT
PG	1/4 NPT
h	57.15 mm
Housing	SSAFS 044 KA
Bearing	23044 CCK/W33
Adapter sleeve assembly	SNW 3044×8
Stabilizing ring	2 x 36053-140
Labyrinth ring	2 x LOR 168
PosiTrac Plus contact element	2 x B10724-167
End plug (suffix Y)	EPR 23
Max. speed for PosiTrac Plus seal	725 r/min
P60°	416 kN

P90°	249 kN
P120°	151 kN
P150°	136 kN
P180°	160 kN
Pa	59.6 kN
Mass pillow block	214 kg
Cap bolt	1 1/8-7 UNC
Cap bolt recommended tightening torque	1735.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Initial grease fill	1672.65 g