

# ISB SQD 10 C plain bearings

We work 0.0 Inventory N/A Minimum Buy Quantity closely with our ISB SQD 10 C plain bearings manufacturing partners to bring the best value to customers.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 0.49   |
| EAN                       | 0782475985920  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Tap Base Pillow Block   |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Polymer  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 7/16 Inch  |
| Relubricatable            | Yes  |
| Insert Part Number        | INS-SC-104S-CR   |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Normal Duty   Corrosion Resistant   |
| Long Description          | 2 Bolt Tap Base Pillow Block; 1-1/4" Bore; 1-11/16" Base to Center Height; Set Screw Mount |
| UNSPSC                    | 31171511   |

|                               |                                |
|-------------------------------|--------------------------------|
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | TB-SCEZ-104S-PCR               |
| Manufacturer Internal Number  | 127512                         |
| Weight / LBS                  | 1.07                           |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter           |
| B                             | 1.688 Inch   42.875 Millimeter |
| Actual Bolt Center to Center  | 3 Inch   76Millimeter          |
| Nominal Bolt Center to Center | 3 Inch   76 Millimeter         |
| D                             | 1.391 Inch   35.331 Millimeter |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter           |
| d                             | 1.25 Inch   31.75 Millimeter   |