

ISB SQD 14 C plain bearings

LET OUR ISB SQD 14 C plain bearings EXPERTS 60 mm d GET YOU THE PARTS YOU NEED.

d	60 mm
D	95 mm
B	23 mm
C	17.5 mm
T	23 mm
d1	78.5 mm
a	21 mm
rs min	1.5 mm
r1s min	1.5 mm
e	0.43
Y2	1.39
Y0	0.77
Mass	0.58 kg
ISO 355 reference	T4CC060
Dynamic load, C	82 kN
Rating life coefficient, A2	1
Static load, C0	123 kN
Fatigue limit load, Cu	15 kN
Nlim (oil)	4,900 rpm
Nlim (grease)	3,700 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.48 Hz

Characteristic outer ring frequency, BPF0	11.7 Hz
Characteristic inner ring frequency, BRFI	14.3 Hz
da max	67 mm
db min	68.5 mm
Da min	85 mm
Da max	86.5 mm
Db min	91 mm
Ca min	4 mm
Cb min	5.5 mm
ra max	1.5 mm
r1a max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359002966
Product Group	B04334