

ISB SQL 10 C RS-1 plain bearings

With over 10170 full-service stores, our ISB SQL 10 C RS-1 plain bearings 65 Outer Diameter (mm) inventory is extensive and our parts are priced right. within 24 30 Bore Diameter (mm) hours. This helps you maximize your productivity by saving time and your hard-earned 30x65x42 Size (mm) dollars.

| | |
|---------------------|--------------------------|
| Size (mm) | 30x65x42 |
| Bore Diameter (mm) | 30 |
| Outer Diameter (mm) | 65 |
| Width (mm) | 42 |
| d | 30 mm |
| D3 | 65 mm |
| T3 | 42 mm |
| A | 0,028 / Factor min. load |
| B | 8 mm |
| C | 7 mm |
| D | 62 mm |
| D1 | 37 mm |
| D2 | 48 mm |
| Da max | 48 mm |
| da max | 35 mm |
| R | 50 mm |
| r1 min | 0,3 mm |
| ra max | 1 mm |
| ra1 max | 0,3 mm |
| rmin | 1 mm |

| | |
|-----|---------------------------------------|
| T2 | 37,8 mm |
| m | 0,749 kg / Weight |
| m1 | 0,057 kg |
| Ca | 35500 N / Dynamic load rating (axial) |
| C0a | 67000 N / Static load rating (axial) |
| nG | 6000 1/min / Limiting speed |
| Cua | 3000 N / Fatigue limit load, axial |