

ISB SS 639/3-ZZ deep groove ball bearings

ISB SS 639/3-ZZ deep groove ball bearings Product Brochures , 0.0 Inventory SKF Manufacturer Name N/A Minimum Buy Quantity Manufacturing Service . Get Your Free.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	6.26
EAN	7316570803587
Product Group	B04286
Stud Profile	Male
Mounting Thread	M60 X 4
Thread Direction	Left Hand
Rolling Element	Spherical Plain
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Steel
Relubricatable	Yes
Enclosure	2 Seals
Other Features	3 Piece Zinc Plated Outer Double Lip Seals
Long Description	60MM Bore; 39MM House Width; Male Stud Profile; M60 X 4; Left Hand Thread Direction; Spherical Plain
Inch – Metric	Metric
UNSPSC	31171508

Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer Item Number	SAL 60 ES-2RS
Weight / LBS	13.779
d	60 mm
Housing Width	1.535 Inch 39 Millimeter
Ball Width	1.732 Inch 44 Millimeter
bore diameter:	60 mm
ball material:	Steel
misalignment angle:	6 °
race material:	Steel
shank thread length:	120 mm
radial static load capacity:	360 kN
rod end type:	Male Threaded
operating temperature range:	-50 to +300 °C
shank thread size:	M60x4
head diameter:	137 mm
thread direction:	Right Hand
head width:	39 mm
lubrication type:	With Lubrication Fitting
ball width:	44 mm
housing material:	Zinc-Plated Steel
length to ball center:	225 mm
d2 max.	137 mm
B	44 mm
G	M 60x4
C1 max.	39 mm

h	225 mm
α	6 °
dk	80 mm
l1 min.	120 mm
l2 max.	296 mm
l7 min.	73 mm
r1 min.	1 mm
Basic dynamic load rating C	245 kN
Basic static load rating C0	360 kN
Specific dynamic load factor K	100 N/mm ²
Material constant KM	330
Mass rod end	6.25 kg