

ISB SX 0118/500 thrust roller bearings

Can't find what you're looking for ISB SX 0118/500 thrust roller bearings ? Our expert Representatives 33,337 Bore Diameter (mm) be in contact with 33,337 mm d you shortly!

Bore Diameter (mm)	33,337
d	33,337 mm
s1	25.4 mm
A	45 mm
A1	27 mm
B	42,9 mm
G	12 mm
H	93 mm
H1	47.6 mm
H2	19 mm
J	126 mm
L	160 mm
N	21 mm
N1	14 mm
Weight	1,65 Kg
Basic dynamic load rating (C)	25,5 kN
Basic static load rating (C0)	15,3 kN
Fatigue load limit (Pu)	0,655
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.59

EAN	7316577755612
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	YAR 207-105-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Single Row Standard Duty Wide Inner Race Y Bearing Has Flinger
Long Description	2 Bolt Pillow Block; 1-5/16" Bore; 1-7/8" Base to Center Height; Set Screw Mount; Ball Bea
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 1.5/16 TF
Weight / LBS	3.5
Bolt Spacing Minimum	4.688 Inch 119.075Millimeter
Length Thru Bore	1.688 Inch 42.87 Millimeter
Bolt Spacing Maximum	5.25 Inch 133.35Millimeter

Actual Bolt Center to Center	0 Inch 0Millimeter
Bore	1.313 Inch 33.35 Millimeter
Base to Center Height	1.875 Inch 47.63 Millimeter
Nominal Bolt Center to Center	5 Inch 127 Millimeter
Housing material	Cast iron
A5	24.5 mm
B4	6 mm
J max.	133 mm
J min.	119 mm
RG	1/4-28 UNF
R1	3 mm
R α	45 °
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	146 mm
J7	15.5 mm
N4	4 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C0	15.3 kN
Fatigue load limit Pu	0.655 kN
Limiting speed	5300 r/min
Mass bearing unit	1.6 kg
Thread grub screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm

Recommended diameter for attachment bolts, inch G	0.5 in
Housing	SY 507 M
Bearing	YAR 207-105-2F
End cover	ECY 207