

# ISB T.P.N. 395 plain bearings

Advance ISB T.P.N. 395 plain bearings is your source for quality and accessories. 60x60x43 Size (mm) shop online for home delivery or pick up in one of our 10000 .

Size (mm)	60x60x43
Bore Diameter (mm)	60
Outer Diameter (mm)	60
Width (mm)	43
d	60 mm
A	60 mm
A1	43 mm
H	29.5 mm
H1	69.9 mm
H2	26.5 mm
L	240 mm
J	190.5 mm
N1	18 mm
B	65.1 mm
s1	39.7 mm
Basic dynamic load rating – C	52.7 kN
Basic static load rating – C0	36 kN
Limiting speed	100 r/min
Limiting temperature – T	350 °C
Mass bearing unit	4.5 kg
Grub (set) screw – G2	M10x1
Hexagonal key size for grub screw – H	5 mm

Recommended tightening torque for grub screw	16.5 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	4.734
EAN	7316571382418
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	16 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 212-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Metric
Other Features	Single Row   Standard Duty   Wide Inner Race   Y Bearing   Has Flinger
Long Description	2 Bolt Pillow Block; 60MM Bore; 70MM Base to Center Height; Set Screw Mount; Ball Bearing; Relubrica
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing

Keyword String	Pillow Block
Manufacturer Item Number	SY 60 TF/VA228
Weight / LBS	9.81
Bolt Spacing Minimum	0 Inch   0Millimeter
Length Thru Bore	2.563 Inch   65.09 Millimeter
Actual Bolt Center to Center	7.5 Inch   190Millimeter
Bore	2.362 Inch   60 Millimeter
Base to Center Height	2.756 Inch   70 Millimeter
Bolt Spacing Maximum	0 Inch   0Millimeter
Nominal Bolt Center to Center	7.3 Inch   184 Millimeter
mounting:	Two-Bolt Base
overall height:	139.5 mm
bore diameter:	60 mm
finish/coating:	Uncoated
bore type:	Round
radial static load capacity:	36 kN
base to bore centerline:	2.7520 in
base width:	60 mm
housing material:	Cast Iron
bolt center-to-center length:	190.5 mm
locking device:	Set Screw
lubrication type:	Lubrication Fitting
expansion type:	Non-Expansion Bearing (Fixed)
series:	SY
overall length:	240 mm
standards met:	ISO
N	29.5 mm

Basic dynamic load rating C	52.7 kN
Basic static load rating C <sub>0</sub>	36 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Attachment bolts, recommended metric size G	16 mm
Bearing	YAR 212-2FW/VA228