

# ISO 21316 KCW33+H316 spherical roller bearings

Request A Quote For Your Special 122.237 mm da ISO 21316 KCW33+H316 spherical roller bearings Needs Today! Free Quotes. ISO 9001 certified.

da	122.237 mm
Da	299.999 mm
Ca	111.785 mm
A1	171.45 mm
A2	307.975 mm
S	4.763 mm
ba	78.581 mm
H	360.363 mm
H1	179.375 mm
H2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J1	107.95 mm
L	628.65 mm
N1	28.575 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	65.088 mm
Housing	SAF 628
Bearing	22328 CCK/W33

Adapter sleeve assembly	SNW 128×4.13/16
Stabilizing ring	SR-0-28
Taconite seal	TER 120
End plug (suffix Y)	EPR 27
Max. speed for Taconite seal	625 r/min
P60°	234 kN
P90°	140 kN
P120°	85.9 kN
P150°	77 kN
P180°	92.5 kN
Pa	42.9 kN
Mass pillow block	134 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g