

ISO 21322 KCW33+H322 spherical roller bearings

are a Cylindrical Bore Bore Type few brands you will Single Shield with Snap Ring Enclosure find in our inventory. Find ISO 21322 KCW33+H322 spherical roller bearings to Single Row Configuration see what's in stock!

| | |
|----------------------------|------------------------------|
| Enclosure | Single Shield with Snap Ring |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Weight | 1.150 kg |
| d | 120 mm |
| D | 165 mm |
| B | 22 mm |
| Fillet Radius/Chamfer | 1.1 mm |
| r1 | 0.5 mm |
| Snap Ring Width | 1.7 mm |
| Snap Ring Outside Diameter | 171.5 mm |
| D1 (max) | 161.8 mm |
| a (max) | 3.7 mm |
| b (min) | 1.9 mm |
| Dynamic Load Rating | 53,000 N |
| Static Load Rating | 54,000 N |
| Limiting Speed – Grease | 3,800 rpm |
| Limiting Speed – Oil | 4,600 rpm |
| Factor fo | 16.5 |
| Radial Clearance | 0.015 to 0.041 mm |
| da (min) | 126 mm |

| | |
|----------|--------|
| Da (max) | 159 mm |
| Dx (min) | 173 mm |
| ra (max) | 1 mm |
| Cy (max) | 5.1 mm |