

# ISO 22309 KCW33+H2309 spherical roller bearings

Shop ISO 22309 KCW33+H2309 spherical roller bearings huge N/A Minimum Buy Quantity online discount inventory. and 0.0 Inventory Import machinery parts your car needs with Free ASAHI BEARINGS Manufacturer Name Shipping and Free Extended Warranty.

|                           |                         |
|---------------------------|-------------------------|
| Inventory                 | 0.0                     |
| Manufacturer Name         | ASAHI BEARINGS          |
| Minimum Buy Quantity      | N/A                     |
| Weight                    | 3.2                     |
| EAN                       | 0808250317011           |
| Product Group             | M06110                  |
| Number of Mounting Holes  | 2                       |
| Mounting Method           | Set Screw               |
| Housing Style             | 2 Bolt Flange Block     |
| Rolling Element           | Ball Bearing            |
| Housing Material          | Nickel Coated Cast Iron |
| Expansion / Non-expansion | Non-expansion           |
| Mounting Bolts            | 5/8 Inch                |
| Relubricatable            | Yes                     |
| Insert Part Number        | MUC211-35               |
| Seals                     | Contact Seal            |
| Housing Configuration     | 1 Piece Solid           |
| Pilot Configuration       | No Pilot                |
| Inch – Metric             | Inch                    |

|                                    |   |
|------------------------------------|---|
| Long Description                   | 2 Bolt Flange Block; 2-3/16" Bore; 7.3" Bolt Circle; 7-1/4" Bolt Spacing; 1 Piece Sol |
| Other Features                     | Single Row   Spherical   Normal Duty   Has Slinger                                    |
| UNSPSC                             | 31171501  |
| Harmonized Tariff Code             | 8483.20.40.40   |
| Noun                               | Bearing   |
| Keyword String                     | Flanged   |
| Weight / LBS                       | 7.05  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter   |
| Bolt Spacing                       | 7.25 Inch   184.15 Millimeter   |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter   |
| D                                  | 2.189 Inch   55.6 Millimeter  |
| d                                  | 2.188 Inch   55.575 Millimeter  |
| Nominal Bolt Circle Diameter Round | 7.3 Inch   184.2 Millimeter   |