

ISO 22326 KCW33+AH2326 spherical roller bearings

We work closely with our ISO 22326 KCW33+AH2326 spherical roller bearings manufacturing 4-7/16 in Shaft Size partners to bring Mounted Bearing Engineering Group the best value to customers.

| | |
|--------------------------|-----------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 4-7/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QVVPN26V407SB |
| Locking Style | Double V-Lock |
| Weight | 136 lb |
| Housing Style | Two-Bolt Pillow Block |
| UPC Code | 0883450080170 |
| Dimension A | 5.91 in |
| Dimension B | 11.09 in |
| Dimension C | 6.88 in |
| Dimension D Max | 15.75 in |
| Dimension D Min | 14.46 in |
| Dimension F | 17.50 in |
| Dimension G | 5.040 in |
| Dimension H | 1.94 in |
| Dimension J (Bolt Size) | 1.000 in |
| Dimension L | 6.03 in |
| Dimension RVV | 0.99 in |
| Dimension SVV | 7.02 in |
| C – Dynamic Load (Basic) | 170000 lb |

| | |
|-------------------------------------|-----------|
| C0 – Static Load | 212000 lb |
| e – Geometry Factor | 0.26 |
| Y1 – Geometry Factor | 2.62 |
| Y2 – Geometry Factor | 3.90 |
| Oil Lubrication – M/N Seal | 700 rpm |
| Oil Lubrication – T Seal | 1500 rpm |
| Oil Lubrication – B/C/O Seal | 400 rpm |
| Grease Lubrication – M/N Seal | 700 rpm |
| Grease Lubrication – T Seal | 1000 rpm |
| Grease Lubrication – B/C/O Seal | 400 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0050 in |
| Eng Internal Radial Clearance – Min | 0.0053 |
| Eng Internal Radial Clearance – Max | 0.0067 |
| Pre Install Clearance Min | 0.0053 in |
| Pre Install Clearance Max | 0.0067 in |