

# ISO 230/500 KW33 spherical roller bearings

The online ISO 230/500 KW33 spherical roller bearings parts store gives N/A Minimum Buy Quantity you immediate access to a selection of more than 1.4 0.0 Inventory million new, used, remanufactured.

|                           |                                                                                 |
|---------------------------|---------------------------------------------------------------------------------|
| Inventory                 | 0.0                                                                             |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC                                                   |
| Minimum Buy Quantity      | N/A                                                                             |
| Weight                    | 17.252                                                                          |
| EAN                       | 0782475698400                                                                   |
| Product Group             | M06288                                                                          |
| Number of Mounting Holes  | 2                                                                               |
| Mounting Method           | Concentric Collar                                                               |
| Housing Style             | 2 Bolt Pillow Block                                                             |
| Rolling Element           | Tapered Roller Bearing                                                          |
| Housing Material          | Cast Iron                                                                       |
| Expansion / Non-expansion | Expansion                                                                       |
| Mounting Bolts            | 3/4 Inch                                                                        |
| Relubricatable            | Yes                                                                             |
| Insert Part Number        | S1U-K-212R                                                                      |
| Seals                     | Land Riding Rubbing Single Lip Contact                                          |
| Housing Configuration     | 2 Piece Split                                                                   |
| Inch – Metric             | Inch                                                                            |
| Other Features            | Double Row   Heavy Duty   Optional E-Tect Seal   Double Collar   With Set Screw |

|                               |                                                                                                  |
|-------------------------------|--------------------------------------------------------------------------------------------------|
| Long Description              | 2 Bolt Pillow Block; 2-3/4" Bore;<br>3-3/4" Base to Center Height;<br>Concentric Collar Mount; T |
| UNSPSC                        | 31171511                                                                                         |
| Harmonized Tariff Code        | 8483.20.40.80                                                                                    |
| Noun                          | Bearing                                                                                          |
| Keyword String                | Pillow Block                                                                                     |
| Manufacturer Item Number      | P2B-K-212RE TYPE K                                                                               |
| Manufacturer Internal Number  | 023204                                                                                           |
| Weight / LBS                  | 40                                                                                               |
| D                             | 3.781 Inch   96.037 Millimeter                                                                   |
| B                             | 3.75 Inch   95.25 Millimeter                                                                     |
| Bolt Spacing Maximum          | 11.5 Inch   292.1Millimeter                                                                      |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter                                                                             |
| d                             | 2.75 Inch   69.85 Millimeter                                                                     |
| Nominal Bolt Center to Center | 10.7 Inch   271.5 Millimeter                                                                     |
| Bolt Spacing Minimum          | 9.875 Inch   250.83Millimeter                                                                    |