

# ISO 230/630 KW33 spherical roller bearings

ISO 230/630 KW33 spherical roller bearings, Units 47 Outer Diameter (mm) and Housings CAD models , Manufacturing Service . 20x47x14 Size (mm) Get Your Free.

Size (mm)	20x47x14
Bore Diameter (mm)	20
Outer Diameter (mm)	47
Width (mm)	14
d	20 mm
D	47 mm
B	14 mm
C	14 mm
r min.	1 mm
da min.	26 mm
Da max.	41 mm
ra max.	1.0 mm
Weight	0.106 Kg
Basic dynamic load rating (C)	12,8 kN
Basic static load rating (C0)	6,6 kN
(Grease) Lubrication Speed	14000 r/min
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	1 Metal Shield

Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Width; 1 Metal Shield; Ball Bearing; ABEC 1   ISO
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.234
Bore	0.787 Inch   20 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	1.85 Inch   47 Millimeter
Outer Race Width	0.551 Inch   14 Millimeter