

ISO 29412 M thrust roller bearings

YOU'LL TIMKEN Manufacturer Name FIND AN EXTENSIVE SELECTION OF ISO 29412 M thrust roller bearings FOR SALE. 0.0 Inventory

| | |
|---------------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 33.06 |
| EAN | 0013992052476 |
| Product Group | B04144 |
| Number of Mounting Holes | 2 |
| Mounting Method | Clamp Collar |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Cylindrical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-Expansion |
| Mounting Bolts | 24 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | MSE307BR |
| Seals | Triple Lip Labyrinth |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Inch |
| Other Features | Single Row Medium Duty With Support Wide Inner Ring Axial Float |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |

| | |
|-------------------------------|--------------------------------------|
| Noun | Bearing |
| Keyword String | Pillow Block |
| Weight / LBS | 72.82 |
| d | 3.438 Inch 87.325 Millimeter |
| Nominal Bolt Center to Center | 13.9 Inch 354 Millimeter |
| Bolt Spacing Maximum | 0 Inch 0Millimeter |
| Actual Bolt Center to Center | 13.9 Inch 354Millimeter |
| Bolt Spacing Minimum | 0 Inch 0Millimeter |
| D | 3.531 Inch 89.7 Millimeter |
| B | 4.921 Inch 125 Millimeter |
| Shaft Size | 3-7/16 in |
| Seal Type | Aluminium Triple Labyrinth |
| Bearing Type | Split Cylindrical Retained Type |
| Support Type | Four-Bolt Plummer Block |
| Series Type | Medium Series |
| Pillow/Plummer Block Style | Split Cylindrical Housed Unit – SAFQ |
| Bolt Size | 4 x 3/4 |
| Bearing UPC | 013992032171 |
| Dimension H | 4-1/2 in |
| Dimension H2 | 9.95 in |
| Dimension J1 | 13-13/64 in |
| Dimension J2 | 11-47/64 in |
| Dimension K | 2-3/8 in |
| Dimension L | 15-23/64 in |
| Dimension M | 4-11/32 in |
| Housing Width | 6.1 in |
| Cr – Dynamic Load Rating | 66830 lbf |
| Cor – Static Load Rating | 79315 lbf |

| | |
|---------------|---|
| Maximum Speed | 2520 rpm |
| Note | This product line was formerly known as "Revolvo" |