

ISO 53211U+U211 thrust ball bearings

ISO 53211U+U211 thrust ball bearings with easy-to-use parts graphics, giving you the thrust washer Bearing Type ability to check parts availability, pricing, examine remanufactured options. 36 Bore Diameter (mm)

Bore Diameter (mm)	36
Outer Diameter (mm)	62
Bearing Type	thrust washer
Shaft Dia., Nominal (d)	36.0000
Bearing Outside Diameter, Nominal(Do)	62.000
Washer Inside Diameter, Nominal (di)	38
Washer Inside Diameter Tolerance (di tol.) – +0.25 / -0	+0.25 / 0
Washer Outside Diameter, Nominal (Do)	62
Washer Outside Diameter Tolerance (Do tol.) – +0 / -0.25	+0 / 0.25
Washer Thickness, Nominal (S3)	2
Washer Thickness Tolerance (S3 tol.) – +0 / -0.05	+0 / 0.05
Mounting Hole Dia. (dm)	4.000
Mounting Hole Pitch Dia. (dp)	50
Housing Counterbore Depth (Ha)	1.00
Housing Counterbore Depth Tolerance (Ha tol.) – +0.2 / -0.2	+0.2 / 0.2
Housing Counterbore Diameter, Nominal (HD)	62.000
Housing Counterbore Diameter Tolerance (HD tol.)	+0.12 / 0

Material	Carbon steel shell with POM plastic liner
----------	---