

ISO 54232U+U232 thrust ball bearings

Can't find what you're 200 mm d looking for ISO 54232U+U232 thrust ball bearings ? Our expert Representatives be in contact with you 310 mm D shortly!

d	200 mm
D	310 mm
B	51 mm
rs min	2.1 mm
Radial clearance class	C4
Mass	11.9 kg
Dynamic load, C	218 kN
Static load, C ₀	243 kN
Fatigue limit load, C _u	6.9 kN
f ₀	15.6
N _{lim} (oil)	2,400 rpm
N _{lim} (grease)	2,000 rpm
Min operating temperature, T _{min}	-60 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.52 Hz
Characteristic outer ring frequency, BPF ₀	6.08 Hz
Characteristic inner ring frequency, BRF ₁	7.92 Hz
da min	211 mm
Da max	299 mm

ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	14
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Brass
Internal Clearance	C4-Extra Loose
Inch – Metric	Metric
Long Description	200MM Bore; 310MM Outside Diameter; 51MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove Riveted Solid Cage
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	31.812
Outside Diameter	12.205 Inch 310 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	2.008 Inch 51 Millimeter

Bore

7.874 Inch | 200
Millimeter